

DATA SHEET

item no. **BNCC5,1C**

connector type
For cable

BNC Male Compression Connector
VSHD 113

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating	5 A
Shielding Effectiveness	> 115 dB @ 1GHz



Return Loss (IEC 169.1.1)
(RF Analyzer E8357A)

0.3 - 500 MHz	- 33.7 dB
500 - 860 MHz	- 30.1 dB
860 - 1000 MHz	- 26.6 dB
1000 - 1750 MHz	- 24.0 dB
1750 - 2150 MHz	- 21.5 dB
2150 - 3000 MHz	- 18.1 dB

Insertion Loss Max.

0.3 - 500 MHz	< 0.06 dB
500 - 860 MHz	< 0.10 dB
860 - 1000 MHz	< 0.14 dB
1000 - 1750 MHz	< 0.18 dB
1750 - 2150 MHz	< 0.19 dB
2150 - 3000 MHz	< 0.22 dB

Temperature

Installing	- 5° to + 50° C
Operating	- 40° to + 100° C
Storing	- 40° to + 100° C

Inner Conductor

Resistance max. @1 A DC **<1 mOhm**

Max. Tensile Strength

Overall **250 N**

Base Material

Body parts	Brass CuZn 39Pb3 / ZINC
Inner conductor	Brass CuZn 39Pb3

Inner Conductor

O-ring **EPDM**

Plating

Body parts	Nitin
Inner conductor	Gold

Color **BLUE**

Date of release **June 05 . 2014**



ITALIANA CONDUTTORI S.r.l.

Viale Zanotti, 90

I - 27027 Gropello Cairoli (PV)

Tel. +39 0382 815 150 - Fax +39 0382 814 970

www.cavel.com - cavel@cavel.it