

Description

Double Shielded Coaxial Cable, for transport and distribution - 75 Ohm
Outdoor and Underground installation cable (Screening Attenuation - Class A)



Data Sheet

17/73FC



Ø	1,63	7,20				10,10
	(Cu)	(PEG)	(Cu/Pet)	(Cu)	(Jelly2)	(PE)

Class CPR acc. to UE 305/2011 (DoP)

Fca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

EN50117-11-2 CEI-UNEL 36762

Reaction to Fire

EN50575

Application

CATV
Exterior and Underground Installation

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,63 ± 0,03	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 7,20 ± 0,10	mm
Copper/Polyester tape longitudinally overlapped	(Cu/Pet)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of annealed copper wires	(Cu)		
Braid optical coverage (IEC 96-1)		64	%
Tracer Identifier	Year + Flag		
Water repellent sealing (sheath)	(Jelly2)		
Diameter over Braid		Ø 7,78	mm
Outer sheath of Polyethylene - black (RAL 9011) - with carbonblack	(PE)	Ø 10,10 ± 0,15	mm

Printed each meter by yellow ink-jet :

CAVEL 1.7/7.3 FC MADE IN ITALY 75 Ohm Euroclass Fca EN50117-11-2 SA Class A CEI-UNEL 36762 C-4 (U0 = 400V) gggaa(n) m

(gggaan=batch number m=meter marking)

Physical data

Weight of copper conductors	39,99	kg/km
Total weight of cable	88,19	kg/km
Minimum bending radius (single/repeated bending)	100	mm
Maximum cable pulling strength	300	N
Minimum installation temperature	-5	°C
Operating temperature	-40 / +80	°C

Electrical data

Characteristic impedance	200 MHz	75 ± 2	Ohm
--------------------------	---------	--------	-----

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

31/07/2023

Responsible

A. Bergaglio

Description

Double Shielded Coaxial Cable, for transport and distribution - 75 Ohm
 Outdoor and Underground installation cable (Screening Attenuation - Class A)



Data Sheet

17/73FC

Velocity Ratio		85 %	
Inner conductor resistance		8,50	Ohm/km
Outer conductor resistance		9,50	Ohm/km
Loop resistance		18	Ohm/km
Sheat Insulation voltage (spark test)		8	kV
Maximum current (I _{eff})		16	A
Structural return loss (SRL)			
5 - 470 MHz	>30 dB		
470 - 1000 MHz	>28 dB		
1000 - 2000 MHz	>23 dB		
2000 - 3000 MHz	>20 dB		

Screening Attenuation (SA)	SA-Class A	Transfer Impedance (Z _t)	
30 - 1000 MHz	>85 dB	5 - 30 MHz	< 7 mΩ/m
1000 - 2000 MHz	>85 dB		
2000 - 3000 MHz	>80 dB		

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,10	690	10,50
10	1,50	1000	13,00
30	2,20	1750	17,90
50	2,80	2150	20,00
200	5,50	2400	22,00
300	6,90	3000	25,00
470	8,80		

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
 Tel +39-382.815150 Fax +39-0382.814212

Date

31/07/2023

Responsible

A. Bergaglio

Description

Double Shielded Coaxial Cable, for transport and distribution - 75 Ohm
Outdoor and Underground installation cable (Screening Attenuation - Class A)

**Data Sheet****17/73FC****Connectors**

3,5/12M-TL232	3,5/12" connector, male, for UNDERGROUND (Hardline) installation -
5/8MU-TL232	5/8" connector, male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 69,0 mm x 20,5 mm
C75-5L	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation
CCFM75GI	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation
CS17	Stripper for Distribution Cables, male, Tools -
DR01	Adapter, Nut and Washer, for INDOOR installation
F163	Series F Crimp, F Crimp, for INDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm
F81-HQ	Adapter, F Adapter FF, for INDOOR installation
FA17/73	Series F Twist-On, F Twist-On, for INDOOR installation, nitin-plated brass - 33,0 mm x 14,5 mm
FC11QM	Series F Compression, Quick Mount, for OUTDOOR installation
FM-FF90	Adapter, FM - FF 90°, for INDOOR installation
FM-TL232	Series F, male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 76,0 mm x 31,0 mm
IEC14M-32	Series IEC (toolless), male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 64,5 mm x 21,0 mm
LTE790	Indoor Fittings, Filter, for INDOOR installation
MM-F703	Adapter, F Adapter MM, for INDOOR installation
MM-FR703	Adapter, F Adapter MM, for INDOOR installation
NM-32	N Connector, male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 62,5 mm x 21,0 mm
SAT2VS	Indoor Fittings, F SAT 2-way Splitter, for INDOOR installation
SR01-32	Adapter, for 11/50 - RG11, for UNDERGROUND (Hardline) installation

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

31/07/2023

Responsible

A. Bergaglio