

DATA SHEET

item no. **FCEM7.0C**

connector type
For cable

F Male Compression Connector
RP705B, TS61L, RP913B, RP65B, DG113
SAT703 or other cables $6,5 < \varnothing < 7$ mm

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating	5 A
Shielding Effectiveness	> 115 dB @ 1GHz



Return Loss (IEC 169.1.1)
(RF Analyzer E8357A)

0.3 - 500 MHz	- 45.3 dB
500 - 860 MHz	- 41.0 dB
860 - 1000 MHz	- 37.3 dB
1000 - 1750 MHz	- 34.7 dB
1750 - 2150 MHz	- 31.9 dB
2150 - 3000 MHz	- 30.5 dB

Insertion Loss Max.

0.3 - 500 MHz	< 0.01 dB
500 - 860 MHz	< 0.01 dB
860 - 1000 MHz	< 0.01 dB
1000 - 1750 MHz	< 0.01 dB
1750 - 2150 MHz	< 0.01 dB
2150 - 3000 MHz	< 0.01 dB

Temperature

Installing	- 5° to + 50° C
Operating	- 40° to + 100° C
Storing	- 40° to + 100° C

Inner Conductor

Resistance max. @1 A DC **<1 mOhm**

Max. Tensile Strength

Overall **250 N**

Base Material

Body parts	Brass CuZn 39Pb3
Inner conductor	Brass CuZn 39Pb3

Inner Conductor

O-ring **EPDM**

Plating

Body parts	Nitin
Inner conductor	Nitin

Color **BULE / BLACK**

Date of release **March 30 . 2016**



ITALIANA CONDUTTORI S.r.l.

Viale Zanotti, 90

I - 27027 Gropello Cairoli (PV)

Tel. +39 0382 815 150 - Fax +39 0382 814 970

www.cavel.com - cavel@cavel.it