

Description


Local Area Network Cable

Cat. 6 U/UTP 4x2xAWG23/1 PVC+PE



Data Sheet

LAN6402G



Ø	0,55	1,05	6,80	8,00
	(Cu)	(PE)	(PVC)	(PE)

Class CPR acc. to UE 305/2011 (DoP)

Fca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

ISO/IEC 11801 Class E	EN 50288-6-1	EN 50173	EIA-TIA 568
CEI-UNEL 36762			

Reaction to Fire

EN50575

Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)

IPTV; HbbTV 2.0.n

IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T

IEEE 802.5 16 MB: ISDN; TPDDI; ATM; PoE

Exterior and Underground Installation

Construction data

4 pairs with conductor of bare copper wires	(Cu)	Ø 0,55	mm
Insulation of solid Polyethylene	(PE)	Ø 1,05	mm

Composition

Twisted pairs, coloured by Standard TIA-568A

Plastic Cross Separator

Inner sheath of Polyvinylchloride - white - lead-free (PVC) Ø 6,80 mm

Outer sheath of Polyethylene - black (RAL 9011) (PE) Ø 8,00 mm

Printed each meter by blue ink-jet :

**CAVEL LAN 640 2G MADE IN ITALY CAT 6 U/UTP 4x2xAWG23 Euroclass Fca ISO-IEC 11801 EN50173
CEI-UNEL 36762 C-4 (U0 = 400V) gggaa(n) m**

(gggaan=batch number m=meter marking)

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

17/07/2023

Responsible

A. Bergaglio

Description

Local Area Network Cable

Cat. 6 U/UTP 4x2xAWG23/1 PVC+PE



Data Sheet

LAN6402G

Physical data

Weight of copper conductors	17,30	kg/km
Total weight of cable	59,90	kg/km
Minimum bending radius x1/n	35/70	mm
Maximum cable pulling strength	100	N
Maximum tensile strength during the installation	100	N
Installation temperature	0 / +50	°C
Operating temperature	-40 / +80	°C

Electrical data

Characteristic impedance	100 MHz	100 ± 5	Ohm
Capacitance of Twisted Pair (@800Hz)		48	pF/m
Velocity Ratio		67 %	
DC Conductor Resistance		82	Ohm/km
Loop resistance		164	Ohm/km
Insulation resistance		> 5000	MOhm x km
Sheath Insulation Voltage (DC, 1 min)		3	kV
Coupling Attenuation		> 45	dB

Transmission-Characteristic (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	RL [dB]	NEXT [dB]	ACR-N [dB/100m]	ACR-F [dB]
1	1,80	25,00	80,00	78,20	75,00
10	5,40	25,00	75,00	69,60	60,00
20	7,70	25,00	70,00	62,30	50,00
31,2	9,60	25,00	65,00	55,40	47,00
62,5	13,70	25,00	60,00	46,30	40,00
100	17,40	25,00	60,00	42,60	37,00
155,5	21,90	25,00	55,00	33,10	30,00
250	28,10	20,00	50,00	21,90	25,00

Connectors

PLUG6U1.1M Plug RJ45, Plug RJ45 UTP Cat. 6, Plug RJ45 -

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

17/07/2023

Responsible

A. Bergaglio