

Description

Local Area Network Cable

Cat. 6A U/UTP 4x2xAWG23/1


Coaxial Cables

CAVEL®

since 1968

Data Sheet

LAN6A40



Ø	0,57	1,05	6,80
	(Cu)	(PE)	(PVC)

Class CPR acc. to UE 305/2011 (DoP)

Eca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

ISO/IEC 11801 Class Ea

EN 50288-11-1

EN50173

IEC 61156-5

EIA-TIA 568

CEI-UNEL 36762

Reaction to Fire

EN50575

Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)

IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T

IEEE 802.5 16 MB: ISDN; FDDI; ATM

Construction data

4 pairs with conductor of bare copper wires	(Cu)	Ø 0,57	mm
Insulation of solid Polyethylene	(PE)	Ø 1,05	mm
Cross separator in Polyethylene			
Outer sheath of Polyvinylchloride - white (PVC) - lead-free	(PVC)	Ø 6,80	mm
Printed each meter by blue ink-jet :			

CAVEL LAN 6A40 MADE IN ITALY CAT 6A U/UTP 4x2xAWG23 - Euroclass Eca ISO-IEC 11801 EN50173

CEI-UNEL 36762 C-4 (U0 = 400V) gggaan m

(ggg=day)(aa=year)(n=batch) (m=meter marking)

Physical data

Weight of copper conductors	18,56	kg/km
Total weight of cable	45,20	kg/km
Minimum bending radius x1/n	35/70	mm
Maximum tensile strength during the installation	100	N
Installation temperature	0 / +50	°C
Operating temperature	-20 / +60	°C

Electrical data

Characteristic impedance	100 MHz	100 ± 5	Ohm
--------------------------	---------	---------	-----

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

11/11/2020

Responsible

A. Bergaglio

Description

Local Area Network Cable

Cat. 6A U/UTP 4x2xAWG23/1

**Data Sheet****LAN6A40**

Capacitance of Twisted Pair (@800Hz)	48	pF/m
Velocity Ratio	67 %	
DC Conductor Resistance	80	Ohm/km
Loop resistance	160	Ohm/km
Insulation resistance	> 5000	MOhm/km
Sheath Insulation Voltage (DC, 1 min)	1	kV
Coupling Attenuation	> 45	dB

Transmission-Characteristic (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	RL [dB]	NEXT [dB]	ACR-N [dB/100m]
1	1,80	25,00	100,00	98,20
10	5,40	25,00	80,00	74,60
20	7,70	25,00	70,00	62,30
31,2	9,60	25,00	65,00	55,40
62,5	13,70	25,00	60,00	46,30
100	17,40	25,00	60,00	42,60
155,5	21,90	25,00	55,00	33,10
200	25,00	20,00	55,00	30,00
250	28,10	20,00	50,00	21,90
300	30,80	20,00	45,00	14,20
500	40,00	15,00	42,00	2,00

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli

Tel +39-382.815150 Fax +39-0382.814212

Date

11/11/2020

Responsible

A. Bergaglio