

Description

Local Area Network Cable

Cat. 7 S/FTP 4x2xAWG23/1 LSZH - 40% Braid Coverage

**Data Sheet****LAN7454ZHA**

Ø	0,57	1,35		8,00
	(Cu)	(PEG)	(Al/Pet)	(LSZH)

Class CPR acc. to UE 305/2011 (DoP)

Dca s1a,d1,a1

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

Standards

ISO/IEC 11801 Class F

EN 50288-4-1

EN50173

EIA-TIA 568

CEI-UNEL 36762

Reaction to Fire

EN50575

Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)

IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T

IEEE 802.5 16 MB: ISDN; TPDDI; ATM; PoE

Indoor + Outdoor Installation

Construction data

4 pairs with conductor of bare copper wires	(Cu)	Ø 0,57	mm
Insulation of physical foam Polyethylene	(PEG)	Ø 1,35	mm
Al/Pet foil shielded pairs, PIMF mode	(Al/Pet)		

Composition

Twisted pairs, coloured by Standard TIA-568A

Braid of tinned copper wires	(CuSn)		
Braid Optical Coverage		41	%
Outer sheath of Thermoplastic material - orange (RAL 2003) - halogen-free, low smoke, flame retardant and UV-resistant	(LSZH)	Ø 8,00	mm

Printed each meter by blue ink-jet :

CAVEL LAN 7454 ZHA MADE IN ITALY CAT 7 S/FTP 4x2xAWG23/1 Euroclass Dca s1a,d1,a1 ISO-IEC 11801 EN50173-1 CEI-UNEL 36762 C-4 (U0 = 400V) gggaa(n) m

(gggaan=batch number m=meter marking)

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

14/03/2022

Responsible

A. Bergaglio

Description

Local Area Network Cable

Cat. 7 S/FTP 4x2xAWG23/1 LSZH - 40% Braid Coverage



Data Sheet

LAN7454ZHA

Physical data

Weight of copper conductors	24,40	kg/km
Total weight of cable	66,30	kg/km
Minimum bending radius x1/n	40/80	mm
Max.Tensile Strength	150	N
Installation temperature	0 / +50	°C
Operating temperature	-20 / +80	°C

Electrical data

Characteristic impedance	100 MHz	100 ± 5	Ohm
Capacitance of Twisted Pair (@800Hz)		43	pF/m
Velocity Ratio		77 %	
DC Conductor Resistance		73	Ohm/km
Loop resistance		146	Ohm/km
Insulation resistance		> 5000	MOhm x km
Sheath Insulation Voltage (DC, 1 min)		1	kV
Coupling Attenuation		> 45	dB

Screening Attenuation (SA)

30 - 100 MHz	> 80 dB
100 - 600 MHz	> 85 dB

Transfer Impedance (Zt)

1 MHz	< 5 mOhm/m
10 MHz	< 3 mOhm/m
30 MHz	< 3 mOhm/m

Transmission-Characteristic (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	RL [dB]	NEXT [dB]	ACR-N [dB/100m]
1	2,10	25,00	90,00	87,90
4	3,60	25,00	90,00	86,40
10	5,40	25,00	90,00	84,60
16	6,80	25,00	90,00	83,20
20	7,70	25,00	85,00	77,30
31,25	9,60	25,00	85,00	75,40
62,5	13,70	25,00	80,00	66,30
100	17,40	25,00	80,00	62,60
155,5	21,90	25,00	80,00	58,10
250	28,10	25,00	75,00	46,90
450	38,30	25,00	70,00	31,70
600	44,80	20,00	65,00	20,20

Connectors

MGN7A45	Socket RJ45 S/FTP shielded, Shielded, crimp PS-GG45 Nexans, Socket RJ45 -
MTS7A45	Socket RJ45 S/FTP shielded, Shielded, crimp PS-TERA™ Siemon, Socket RJ45 -
PF-24PN	Patch panel, ?Pannello 19" 24 Porte Vuoto per RJ45 FTP 1 HE con, Patch panel UTP -
PLUG6AF	Plug RJ45, Plug RJ45 Cat.6A shielded per conduttori solidi, Plug RJ45

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

14/03/2022

Responsible

A. Bergaglio