

Description

Multimedia Cable

Coaxial cable - 75 Ohm - with twisted pair AWG 24


Coaxial Cables

CAVEL®

since 1968

Data Sheet

SAT501AWG



Ø	0,80	3,5	3,60	4,00	5,00		8,20 x 6,00
	(Cu)	(PEG)	(Al/PET/Al)	(CuSn)	(PVC)	(PET)	(PVC)

Class CPR acc. to UE 305/2011 (DoP)

Fca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/ 2011 for the class of performance specified on the related product label.

Standards

EN50117-9-2

CEI-UNEL 36762

Reaction to Fire

EN50575

Application

Indoor Installation

Construction data

Outer non-migrating Polyester tape longitudinally overlapped (Pet)

Attached Data Sheet

Sheath Colour

SAT501	white
CT19	orange
CT20	white/orange

Outer sheath of Polyvinylchloride - white - lead-free (PVC) Ø 8,20 x 6,00 ± 0,20 mm

Printed each meter by blue ink-jet :

CAVEL SAT 501 AWG MADE IN ITALY 75 Ohm EN50117-9-2 CEI-UNEL 36762 C-4 (U0 = 400V) gggaaan m

(ggg=day)(aa=year)(n=batch) (m=meter marking)

Physical data

Weight of copper conductors	12,54	kg/km
Total weight of cable	46,36	kg/km
Minimum installation temperature	-5	°C
Operating temperature	-20 / +70	°C

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

20/05/2022

Responsible

A. Bergaglio

Description

Multimedia Cable

Coaxial cable - 75 Ohm - with twisted pair AWG 24

Coaxial Cables

CAVEL[®]

since 1968

Data Sheet

SAT501AWG**Connectors**

BNCC3.9C	Series BNC Compression, BNC Compression, for OUTDOOR installation
BNCC501	Series BNC Compression, BNC Compression, for OUTDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm
C75-5L	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation
CCFM75GI	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation
CS00	Stripper for Drop Cables, Standard cables from 5 to 7 mm, Tools -
DR01	Adapter, Nut and Washer, for INDOOR installation
F501	Series F Crimp, Crimp F-59-ALM 3.9/6.4, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
F81-HQ	Adapter, F Adapter FF, for INDOOR installation
FA501	Series F Twist-On, F Twist-On, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
FC5.0QMS	Series F Compression, Short Quick Mount, for OUTDOOR installation
FC501	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass - 30,0 mm x 12,0 mm
FCEM5.0C	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass
FCPO3.9C	Series F Compression, Ø 3,9 Push-On, for OUTDOOR installation, nitin-plated brass
FM-FF90	Adapter, FM - FF 90°, for INDOOR installation
IECF905C	Series IEC (toolless), Ø 3,9 90° female, for INDOOR installation
IECM905C	Series IEC (toolless), Ø 3,9 90° male, for INDOOR installation
LTE790	Indoor Fittings, Filter, for INDOOR installation
MM-F703	Adapter, F Adapter MM, for INDOOR installation
MM-FR703	Adapter, F Adapter MM, for INDOOR installation
SAT2VS	Indoor Fittings, F SAT 2-way Splitter, for INDOOR installation

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli

Tel +39-382.815150 Fax +39-0382.814212

Date

20/05/2022

Responsible

A. Bergaglio

Description

Double Shielded Coaxial Connection Cable for Wide Band - 75 Ohm
Indoor / Outdoor installation cable



Data Sheet

SAT501
SAT501AWG



Ø	0,80 (Cu)	3,50 (PEG)	3,60 (Al/Pet/Al)	4,00 (CuSn)	5,00 (PVC)
---	--------------	---------------	---------------------	----------------	---------------

Class CPR acc. to UE 305/2011 (DoP)

Eca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/ 2011 for the class of performance specified on the related product label.

Standards

EN50117-9-2 CEI-UNEL 36762

Reaction to Fire

EN50575

Application

Indoor Installation

Construction data

Inner conductor of plain copper	(Cu)	Ø 0,80 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 3,50 ± 0,10	mm
Aluminum/Polyester/Aluminum tape longitudinally overlapped	(Al/Pet/Al)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		47	%
Diameter over Braid		Ø 4,00	mm
Outer sheath of Polyvinylchloride - white - lead-free	(PVC)	Ø 5,00 ± 0,10	mm
Printed each meter by blue ink-jet :			

CAVEL SAT 501 MADE IN ITALY 75 Ohm Euroclass Eca EN50117-9-2 CEI-UNEL 36762 C-4 (U0 = 400V) gggaa(n) m

(ggg=day)(aa=year)(n=batch) (m=meter marking)

Physical data

Weight of copper conductors	8,87	kg/km
Total weight of cable	23,90	kg/km
Minimum bending radius (single/repetead bending)	25/50	mm
Maximum cable pulling strength	90	N
Minimum installation temperature	-5	°C
Operating temperature	-20 / +70	°C

Electrical data

Characteristic impedance	200 MHz	75 ± 3	Ohm
--------------------------	---------	--------	-----

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

14/06/2023

Responsible

A. Bergaglio

Description

Double Shielded Coaxial Connection Cable for Wide Band - 75 Ohm
Indoor / Outdoor installation cable



Data Sheet

SAT501
SAT501AWG

Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		35	Ohm/km
Outer conductor resistance		26	Ohm/km
Loop resistance		61	Ohm/km
Sheat Insulation voltage (spark test)		2,50	kV
Maximum current (Ieff)		4	A
Structural return loss (SRL)			
5 - 470 MHz	>30 dB		
470 - 1000 MHz	>27 dB		
1000 - 2000 MHz	>27 dB		
2000 - 3000 MHz	>20 dB		
Screening Attenuation (SA)	SA-Class B	Transfer Impedance (Zt)	
30 - 1000 MHz	>80 dB	5 - 30 MHz	< 23 mOhm/m
1000 - 2000 MHz	>80 dB		
2000 - 3000 MHz	>75 dB		

Connectors

BNCC3.9C	Series BNC Compression, BNC Compression, for OUTDOOR installation
BNCC501	Series BNC Compression, BNC Compression, for OUTDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm
C75-5L	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation
CCFM75GI	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation
CS00	Stripper for Drop Cables, Standard cables from 5 to 7 mm, Tools -
DR01	Adapter, Nut and Washer, for INDOOR installation
F501	Series F Crimp, Crimp F-59-ALM 3.9/6.4, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
F81-HQ	Adapter, F Adapter FF, for INDOOR installation
FA501	Series F Twist-On, F Twist-On, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
FC5.0QMS	Series F Compression, Short Quick Mount, for OUTDOOR installation
FC501	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass - 30,0 mm x 12,0 mm
FCPO3.9C	Series F Compression, Ø 3,9 Push-On, for OUTDOOR installation, nitin-plated brass
FM-FF90	Adapter, FM - FF 90°, for INDOOR installation
IECF905C	Series IEC (toolless), Ø 3,9 90° female, for INDOOR installation
IECM905C	Series IEC (toolless), Ø 3,9 90° male, for INDOOR installation
LTE790	Indoor Fittings, Filter, for INDOOR installation
MM-F703	Adapter, F Adapter MM, for INDOOR installation
MM-FR703	Adapter, F Adapter MM, for INDOOR installation
SAT2VS	Indoor Fittings, F SAT 2-way Splitter, for INDOOR installation

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

14/06/2023

Responsible

A. Bergaglio

Ø	0,51	0,90
	(Cu)	(HDPE)

Application

Construction data

Inner conductor of plain copper	(Cu)	Ø 0,51	mm
Outer sheath of High Density Polyethylene - orange	(HDPE)	Ø 0,90 ± 0,05	mm

Physical data

Copper Content	1,82	kg/km
Cable Weight	2,23	kg/km

Ø	0,51	0,90
	(Cu)	(HDPE)

Application

Construction data

Inner conductor of plain copper	(Cu)	Ø 0,51	mm
Outer sheath of High Density Polyethylene - white/orange	(HDPE)	Ø 0,90	mm

Physical data

Copper Content	1,82	kg/km
Cable Weight	2,24	kg/km

ITALIANA CONDUTTORI s.r.l.Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

Alberto Scardovi