

Description

Triple Shielded Coaxial Cable, for transport and distribution, for digital reception - 75 Ohm
Outdoor and Underground installation cable (Screening attenuation - Class A++)

Coaxial Cables

CAVEL®

since 1968

Data Sheet

TS11J

Ø	1,63	7,20	7,37	7,85	7,97	10,30
	(Cu)	(PEG)	(Al/Pet/Al+Sur)	(CuSn)	(Al/Pet J-foil)	(PE)

Class CPR acc. to UE 305/2011 (DoP)

Fca

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/ 2011 for the class of performance specified on the related product label.

Standards

EN50117-11-2

CEI-UNEL 36762

Reaction to Fire

EN50575

Application

DOCSIS 3.1 (Data Over Coax System)

CATV

4K-UHD

Exterior and Underground Installation

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,63 ± 0,03	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 7,20 ± 0,10	mm
Aluminum/Polyester/Aluminum+Surlyn tape longitudinally overlapped and bonded to the dielectric	(Al/Pet/Al+Sur)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		63	%
Tracer Identifier	Year + Flag		
Aluminum/Polyester j-fold and longitudinally overlapped	(Al/Pet J-foil)		
Diameter under Sheath		Ø 7,97	mm
Outer sheath of Polyethylene - black with two green bands - with carbonblack	(PE)	Ø 10,30 ± 0,20	mm

Printed by yellow ink-jet :

CAVEL TS 11 J MADE IN ITALY 75 Ohm Euroclass Fca EN50117-11-2 SA Class A++ CEI-UNEL 36762 C-4 (U0 = 400V) ULTRA HD / 4K gggaa(n) m

(gggaan=batch number m=meter marking)

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

13/07/2023

Responsible

A. Bergaglio

Description

Triple Shielded Coaxial Cable, for transport and distribution, for digital reception - 75 Ohm
Outdoor and Underground installation cable (Screening attenuation - Class A++)

Coaxial Cables

CAVEL

since 1968

Data Sheet

TS11J**Physical data**

Weight of copper conductors	34,57	kg/km
Total weight of cable	86,70	kg/km
Minimum bending radius (single/repeated bending)	100	mm
Maximum cable pulling strength	300	N
Minimum installation temperature	-5	°C
Operating temperature	-40 / +80	°C

Electrical data

Characteristic impedance	200 MHz	75 ± 2	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		8,50	Ohm/km
Outer conductor resistance		7,50	Ohm/km
Loop resistance		16	Ohm/km
Sheat Insulation voltage (spark test)		8	kV
Maximum current (Ieff)		16	A
Structural return loss (SRL)			
5 - 470 MHz	>30 dB		
470 - 1000 MHz	>28 dB		
1000 - 2000 MHz	>23 dB		
2000 - 3000 MHz	>20 dB		
Screening Attenuation (SA)	SA-Class A++		
30 - 1000 MHz	>110 dB		
1000 - 2000 MHz	>105 dB		
2000 - 3000 MHz	> 85 dB		
	Transfer Impedance (Zt)		
	5 - 30 MHz		< 2,5 mOhm/m

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,10	690	9,90
10	1,50	1000	12,80
30	2,20	1750	17,00
50	2,80	2150	19,40
200	5,20	2400	21,00
300	6,40	3000	24,50
470	8,10		

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

13/07/2023

Responsible

A. Bergaglio

Description

Triple Shielded Coaxial Cable, for transport and distribution, for digital reception - 75 Ohm
Outdoor and Underground installation cable (Screening attenuation - Class A++)



Data Sheet

TS11J**Connectors**

3,5/12M-TL232	3,5/12" connector, male, for UNDERGROUND (Hardline) installation -
5/8MU-TL232	5/8" connector, male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 69,0 mm x 20,5 mm
C75-5L	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation
CCFM75GI	Indoor Fittings, 75 Ohm Terminator, for INDOOR installation
CS17	Stripper for Distribution Cables, male, Tools -
DR01	Adapter, Nut and Washer, for INDOOR installation
F163	Series F Crimp, F Crimp, for INDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm
F81-HQ	Adapter, F Adapter FF, for INDOOR installation
FA17/73	Series F Twist-On, F Twist-On, for INDOOR installation, nitin-plated brass - 33,0 mm x 14,5 mm
FC11QM	Series F Compression, Quick Mount, for OUTDOOR installation
FM-FF90	Adapter, FM - FF 90°, for INDOOR installation
FM-TL232	Series F, male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 76,0 mm x 31,0 mm
IEC14M-32	Series IEC (toolless), male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 64,5 mm x 21,0 mm
LTE790	Indoor Fittings, Filter, for INDOOR installation
MM-F703	Adapter, F Adapter MM, for INDOOR installation
MM-FR703	Adapter, F Adapter MM, for INDOOR installation
NM-32	N Connector, male, for UNDERGROUND (Hardline) installation, nitin-plated brass - 62,5 mm x 21,0 mm
SAT2VS	Indoor Fittings, F SAT 2-way Splitter, for INDOOR installation
SR01-32	Adapter, for 11/50 - RG11, for UNDERGROUND (Hardline) installation

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

13/07/2023

Responsible

A. Bergaglio