

Description

Triple Shielded Coaxial Drop Cable, for digital reception - 75 Ohm
 Indoor and Outdoor installation cable (Screening attenuation - Class A++)



Data Sheet

TS613B



Ø	1,00	4,60	4,77	5,17	5,29	6,90
	(Cu)	(PEG)	(Al/Pet/Al+Sur)	(CuSn)	(Al/Pet)	(LSZH-FR+)

Class CPR acc. to UE 305/2011 (DoP)

B2ca s1a,d1,a1

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/ 2011 for the class of performance specified on the related product label.

Standards

EN50117-9-2	EN50288-10-2	CEI-UNEL 36762
-------------	--------------	----------------

Reaction to Fire

EN50575

Application

DOCSIS 3.1 (Data Over Coax System)

CATV

4K-UHD

Indoor + Outdoor Installation

Construction data

Inner conductor of plain copper	(Cu)	Ø 1,00 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,60 ± 0,10	mm
Aluminum/Polyester/Aluminum+Surlyn tape longitudinally overlapped and bonded to the dielectric	(Al/Pet/Al+Sur)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		73	%
Outer Aluminum/Polyester tape longitudinally overlapped	(Al/Pet)		
Diameter under Sheath		Ø 5,29	mm
Outer sheath of Thermoplastic material - white - halogen-free, low smoke, flame retardant	(LSZH-FR+)	Ø 6,90 ± 0,15	mm

Printed each meter by blue ink-jet :

CAVEL TS 613 B MADE IN ITALY 75 Ohm Euroclass B2ca s1a,d1,a1 EN50117-9-2 SA Class A++ CEI-UNEL 36762 C-4 (U0 = 400V) ULTRA HD / 4K gggaa(n) m

(gggaan=batch number m=meter marking)

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
 Tel +39-382.815150 Fax +39-0382.814212

Date

08/11/2023

Responsible

A. Bergaglio

Description

Triple Shielded Coaxial Drop Cable, for digital reception - 75 Ohm
 Indoor and Outdoor installation cable (Screening attenuation - Class A++)



Data Sheet

TS613B

Physical data

Weight of copper conductors	17,40	kg/km
Total weight of cable	54,90	kg/km
Minimum bending radius (single/repeated bending)	35/70	mm
Maximum cable pulling strength	120	N
Minimum installation temperature	-5	°C
Operating temperature	-25 / +70	°C

Electrical data

Characteristic impedance	200 MHz	75 ± 3	Ohm
Capacitance (@1kHz)		54 ± 2	pF/m
Velocity Ratio		82 %	
Inner conductor resistance		22,50	Ohm/km
Outer conductor resistance		10,40	Ohm/km
Loop resistance		32,90	Ohm/km
Sheat Insulation voltage (spark test)		3	kV
Maximum current (Ieff)		6	A
Structural return loss (SRL)			
5 - 470 MHz	>30 dB		
470 - 1000 MHz	>28 dB		
1000 - 2000 MHz	>26 dB		
2000 - 3000 MHz	>22 dB		

Screening Attenuation (SA)	SA-Class A++	Transfer Impedance (Zt)	Zt-Class A++
30 - 1000 MHz	> 110 dB	5 - 30 MHz	< 0,9 mOhm/m
1000 - 2000 MHz	> 100 dB		
2000 - 3000 MHz	> 90 dB		

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,70	690	16,70
10	2,30	1000	20,10
30	3,50	1750	27,30
50	4,40	2150	30,60
200	8,60	2400	32,60
300	10,70	3000	37,10
470	13,40		

Connectors

- CS03J** Stripper for Drop Cables, just for RP and TS Cables, Tools -
- FC02** Other Tools, Scissor multi purpose CAVEL, Tools -
- FC7.0QM** Series F Compression, Quick Mount, for OUTDOOR installation
- FCEM7.0C** Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
 Tel +39-382.815150 Fax +39-0382.814212

Date

08/11/2023

Responsible

A. Bergaglio